



MARKET SHARE LEADER*

#1 PASSENGER REPLACEMENT TIRES†

#1 ORIGINAL EQUIPMENT CONSUMER TIRES†

ASSURANCE WEATHERREADY®

PREDICTABLE CONTROL IN EVERY SEASON

■ CONQUER THE CONDITIONS

Take control of Mother Nature with Weather Reactive Technology, which combines Evolving Traction® Grooves to evacuate water and reduce hydroplaning with Tredlock® Technology, complex interlocking biting edges that maximize overall responsiveness.

■ EMBRACE THE ELEMENTS

Maneuver with confidence in tough weather conditions without sacrificing road noise, compliments of an asymmetric tread pattern.

■ WASH AWAY WORRIES

Be prepared for the unexpected with sweeping traction grooves that provide predictable traction by forcing water and delivering excellent wet traction.

■ CORNER WITH CONFIDENCE

Handle turns and curves with ease thanks to full-depth zigzag sipes that provide exceptional handling and traction for the life of the tire.

■ PLOW THROUGH POWDER

Take charge in wet and cold conditions, thanks to an exclusive compound blend that features soy oil for enhanced traction without sacrificing treadwear; severe snow designated.



**See Product Service area on Tire-HQ™ for complete details.



Severe Snow Designation



*Sources: Modern Tire Dealer (2022 Facts Issue Jan 2022) - 2021 Replacement Passenger & Light Truck Tire Brand Market Shares (p. 44); 2021 North American OE Consumer Tire Market Share Brand Totals (p. 48).



ASSURANCE WEATHERREADY® AVAILABLE SIZES

SIZE	SERVICE DESCRIPTION	LOAD RANGE	SIDEWALL	PRODUCT CODE	MATERIAL NUMBER	APPROVED RIM WIDTH (INS)	MEASURING RIM WIDTH (INS)	SECTION WIDTH (INS)	OVERALL DIAMETER (INS)	MAX LOAD (LBS)	REVS/ MILE	TREAD DEPTH (IN 32NDS)	UTQG
195/65R15	91H	SL	VS	767489537	230529	5.5 - 7.0	6.0	7.9	25.0	1,356	836	10	700 A A
195/55R16	87H	SL	VS	767820537	230528	5.5 - 7.0	6.0	7.9	24.4	1,201	856	10	700 A A
205/55R16	91H	SL	VS	767524537	230530	5.5 - 7.5	6.5	8.4	24.9	1,356	840	10	700 A A
205/60R16	92V	SL	VS	767570537	230551	5.5 - 7.5	6.0	8.2	25.7	1,389	814	10	700 A A
205/65R16	95H	SL	VS	767780537	230552	5.5 - 7.5	6.0	8.2	26.5	1,521	790	10	700 A A
215/55R16	97H	XL	VS	767507537	235441	6.0 - 7.5	7.0	8.9	25.3	1,609	827	11	700 A A
215/60R16	95H	SL	VS	767829537	230554	6.0 - 7.5	6.5	8.7	26.1	1,521	800	10	700 A A
215/65R16	98H	SL	VS	767874537	230556	6.0 - 7.5	6.5	8.7	27.0	1,653	774	10	700 A A
215/70R16	100T	SL	VS	767782537	230558	5.5 - 7.0	6.5	8.7	27.9	1,764	750	11	700 A A
225/60R16	98H	SL	VS	767407537	230562	6.0 - 8.0	6.5	9.0	26.6	1,653	785	10	700 A A
225/70R16	103T	SL	VS	767378537	230566	6.0 - 7.5	6.5	9.0	28.4	1,929	735	11	700 A A
215/45R17	87V	SL	VS	767568537	230588	7.0 - 8.0	7.0	8.4	24.7	1,201	848	10	700 A A
215/50R17	95V	XL	VS	767966537	235442	6.0 - 7.5	7.0	8.9	25.5	1,521	819	10	700 A A
215/55R17	94V	SL	VS	767340537	230553	6.0 - 7.5	7.0	8.9	26.3	1,477	795	10	700 A A
215/60R17	96H	SL	VS	767322537	230555	6.0 - 7.5	6.5	8.7	27.2	1,565	769	10	700 A A
215/65R17	99H	SL	VS	767875537	230557	6.0 - 7.5	6.5	8.7	28.0	1,709	746	10	700 A A
225/50R17	94V	SL	VS	767372537	230559	6.0 - 8.0	7.0	9.2	25.9	1,477	807	10	700 A A
225/55R17	97H	SL	VS	767753537	230560	6.0 - 8.0	7.0	9.2	26.8	1,609	781	10	700 A A
225/60R17	99H	SL	VS	767366537	230563	6.0 - 8.0	6.5	9.0	27.6	1,709	756	11	700 A A
225/65R17	102H	SL	VS	767517537	230565	6.0 - 8.0	6.5	9.0	28.5	1,874	733	11	700 A A
235/45R17	97V	XL	VS	767881537	230567	7.5 - 9.0	8.0	9.3	25.4	1,609	824	10	700 A A
235/50R17	96V	SL	VS	767970537	235445	6.5 - 8.5	7.5	9.7	26.3	1,565	795	10	700 A A
235/55R17	99H	SL	VS	767181537	230571	6.5 - 8.5	7.5	9.7	27.2	1,709	769	11	700 A A
235/60R17	102H	SL	VS	767488537	230576	6.5 - 8.5	7.0	9.5	28.1	1,874	744	11	700 A A
235/65R17	104H	SL	VS	767188537	230578	6.5 - 8.5	7.0	9.5	29.1	1,984	719	11	700 A A
215/55R18	95H	SL	VS	767007537	237336	6.0 - 7.5	7.0	8.9	27.3	1,521	766	11	700 A A
225/45R18	95V	XL	VS	767906537	232361	7.0 - 8.5	7.5	8.9	25.9	1,521	806	10	700 A A
225/55R18	98V	SL	VS	767880537	230561	6.0 - 8.0	7.0	9.2	27.8	1,653	753	10	700 A A
225/60R18	100H	SL	VS	767363537	230564	6.0 - 8.0	6.5	9.0	28.6	1,764	730	11	700 A A
235/45R18	94V	SL	VS	767871537	230568	7.5 - 9.0	8.0	9.3	26.3	1,477	793	10	700 A A
235/50R18	97V	SL	VS	767876537	230570	6.5 - 8.5	7.5	9.7	27.3	1,609	766	10	700 A A
235/55R18	100V	SL	VS	767877537	230572	6.5 - 8.5	7.5	9.7	28.2	1,764	742	11	700 A A
235/60R18	103H	SL	VS	767815537	230577	6.5 - 8.5	7.0	9.5	29.1	1,929	718	11	700 A A
235/65R18	106H	SL	VS	767885537	230579	6.5 - 8.5	7.0	9.5	30.0	2,094	696	11	700 A A
245/45R18	100V	XL	VS	767014537	237586	7.5 - 9.0	8.0	9.6	26.7	1,764	784	10	700 A A
245/60R18	105H	SL	VS	767819537	230583	7.0 - 8.5	7.0	9.8	29.6	2,039	707	11	700 A A
255/55R18	109V	XL	VS	767903537	231534	7.0 - 9.0	8.0	10.4	29.0	2,271	720	11	700 A A
255/65R18	111T	SL	VS	767894537	230586	7.0 - 9.0	7.5	10.2	31.1	2,403	673	11	700 A A
265/60R18	110H	SL	VS	767957537	237335	7.5 - 9.5	8.0	10.7	30.5	2,337	685	11	700 A A
235/45R19	95V	SL	VS	767968537	235444	7.5 - 9.0	8.0	9.3	27.4	1,521	764	11	700 A A
235/50R19	99V	SL	VS	767010537	237337	6.5 - 8.5	7.5	9.7	28.3	1,709	738	11	700 A A
235/55R19	101V	SL	VS	767883537	230573	6.5 - 8.5	7.5	9.7	29.2	1,819	716	11	700 A A
245/55R19	103H	SL	VS	767890537	230582	7.0 - 8.5	7.5	10.0	29.7	1,929	705	11	700 A A
255/50R19	107H	XL	VS	767905537	231535	7.0 - 9.0	8.0	10.4	29.1	2,149	718	11	700 A A
255/60R19	109H	SL	VS	767892537	230585	7.0 - 9.0	7.5	10.2	31.1	2,271	673	11	700 A A
235/55R20	102V	SL	VS	767928537	244639	6.5 - 8.5	7.5	9.7	30.2	1,874	693	11	700 A A
245/50R20	102H	SL	VS	767870537	230581	7.0 - 8.5	7.5	10.0	29.7	1,874	704	11	700 A A
255/50R20	109V	XL	VS	767967537	235443	7.0 - 9.0	8.0	10.4	30.1	2,271	695	11	700 A A
255/55R20	110H	XL	VS	767891537	230584	7.0 - 9.0	8.0	10.4	31.0	2,337	674	11	700 A A

POPULAR FITMENTS

- Acura MDX
- Chevrolet Traverse
- Chrysler Pacifica
- Ford Edge
- GMC Acadia
- Honda Passport
- Kia Sorento
- Lexus ES
- Subaru Ascent
- Toyota Highlander
- Volvo XC60
- VW Tiguan

PLUS-SIZING DISCLAIMER WARNING: Before you replace tires, always consult the vehicle owner's manual and follow the vehicle manufacturer's replacement tire recommendations. Vehicle handling may be significantly affected by a change in tire size or type. When selecting tires that are different from the Original Equipment size, see a professional installer in order to make certain that proper clearance, load-carrying capacity and inflation pressure are selected. Never exceed the maximum load capacity and inflation pressure listed on the sidewall of the tire. Always drive safely and obey all traffic laws. Avoid sudden, sharp turns or lane changes. Failure to follow this warning may result in loss of control of the vehicle, leading to an accident and serious injury or death.

For more complete information, go to Tire-HQ™ at www.tire-hq.com.

©2022 The Goodyear Tire & Rubber Company and Goodyear Canada Inc. All rights reserved.



Scan code for product video

GOODYEAR
MORE DRIVEN.